

# BestCoat EP609

Self-leveling Epoxy, Three components.

Apr. 2023 Version

PHỤ GIA & HÓA CHẤT XÂY DỰNG BESTMIX® CONSTRUCTION CHEMICALS & ADMIXTURES  
 CEMENT AID - CONCRETE ADMIXTURE - WATERPROOFING - GROUTING - FLOORING - BONDING - SEALING - REPAIRING - PROTECTING - FINISHING  
 ẨM GIÀ BẾ TÔNG, XI MĂNG - HÓA CHẤT CHỐNG THẤM - VỮA RỐT RỐT KHÔNG CỎ NGÓT - NỀN SÀN - KẾT NỐI - TRÁM BÍT - SỬA CHỮA - BẢO VỆ AN THIÊN - BẢO VỆ AN THIÊN - BẢO VỆ AN THIÊN

<b>Description:</b>	BestCoat EP609 is a self-leveling epoxy, non-solvent, three components. BestCoat EP609 is made from 100% pure epoxy, high strength and selected silicate mineral and other special additives.
<b>Recommended for:</b>	BestCoat EP609 is used for high requirements such as: Resistance to high loading, chemical, corrosion, mechanic and meet the standard requirements of pharmaceutical safety, food, ...as factory floors of pharmaceutical, seafood, food, assembly of electronic components, textiles, sterile room, operating room, laboratory, aircraft hangar, parking,... BestCoat EP609 can be directly applied on natural stone, grindstone, woodl...
<b>Advantages:</b>	<ul style="list-style-type: none"> <li>• Meet the standard of microbiological, food safety, pharmaceutical, GMP, HACCP.</li> <li>• Low viscosity, high self-leveling, easy to apply, high performance.</li> <li>• Resistance to chemical, mechanical abrasion, loading...</li> <li>• Well bonding to various material surfaces.</li> <li>• Easy to clean, wash, anti-microbial, anti- mold...</li> <li>• Friendly to environment.</li> </ul>

## PRODUCT DATA

<b>Package:</b>	20; 40 kg/set.
<b>Shelf life:</b>	12 months in unopened pack.
<b>Color:</b>	Yellow, Green, blue, grey, or as requested.
<b>Density:</b>	Part A: 1.17 kg/liter (@ 25°C) Part B: 0.98 kg/liter (@ 25°C) Part C: 2.60 kg/liter (@ 25°C) Mixed: 1.80 kg/liter (@ 25°C)
<b>Solid content:</b>	100 %
<b>Consumption:</b>	1.80 kg/m <sup>2</sup> /mm thickness.
<b>Application temperature:</b>	Minimum: 15°C (but above dew point temperature of 5°C) Maximum: 35°C Relative humidity Max.: 80%
<b>Chemical resistance:</b>	Resistance to alkali, acid, oil, grease....and other chemical solutions.
<b>Mechanical strength :</b>	High loading capacity and mechanical abrasion resistance.
<b>Mixing ratio:</b>	<b>3: 1: 9 (by weight)</b>

### BESTMIX CORPORATION

www.bestmix.vn

**HEAD OFFICE:**  
 Lot D1, D1&N3 Rd., Nam Tan Uyen IP,  
 Tan Uyen Town, Binh Duong Province,  
 Tel: (027) 4365 3990 - 4365 3991  
 Email: info@bestmix.com.vn

**HCMC OFFICE 1:**  
 378-384 Cong Hoa Str., Ward 13,  
 Tan Binh Dist., Ho Chi Minh City  
 Tel: (028) 3810 7995 (7996, 7997)  
 Email: bm1@bestmix.com.vn

**HCMC OFFICE 2:**  
 23 Nguyen Huu Canh Str., Ward 22,  
 Binh Thanh Dist., Ho Chi Minh City  
 Tel: (028) 3899 0339 - 3899 0340  
 Email: bm2@bestmix.com.vn

**NHA TRANG OFFICE:**  
 989 Le Hong Phong Street,  
 Phuoc Long Ward, Nha Trang City  
 Tel: 090 545 3579  
 Email: bm3@bestmix.com.vn

**CENTRAL BRANCH:**  
 478B1 Dien Bien Phu Street,  
 Thanh Khe District, Da Nang City  
 Tel: (023) 6371 5299 - 6371 5399  
 Email: bm4@bestmix.com.vn

**NORTHERN BRANCH:**  
 TT6.2 - 65, Dai Kim Urban Area,  
 Hoang Mai District, Ha Noi City  
 Tel: (024) 3200 8234  
 Email: bm5@bestmix.com.vn

**Pot-life:**

Ambient temperature	<b>+20°C</b>	<b>+25°C</b>	<b>+30°C</b>	<b>+35°C</b>
Pot-life (Minute)	90	65	40	30

**Curing times:**

Ambient temperature	<b>+20°C</b>	<b>+25°C</b>	<b>+30°C</b>	<b>+35°C</b>
Walk-ability	30 hours	30 hours	24 hours	20 hours
Light mechanical impacts	5 days	4 days	3 days	2 days
Full cure	10 days	10 days	7 days	7 days

**Physical properties:** (curing after 7 days @ 30°C)

Compressive strength (MPa)	≥ 70	Bonding strength (MPa)	≥ 1.5 Concrete failure
Flexural strength (MPa)	≥ 35	Shore hardness D	≥ 70
Abraision resistant (mg) (CS10/1000/1000)	≤ 70	Tensile strength (MPa)	≥ 25

**APPLICATION**

<b>Coating system:</b>	Primer coat of BestPrimer EP601, BestPrimer EP602 or BestPrimer EP603. Top coat of BestCoat EP609 with designed thickness.
<b>Substrate requirement:</b>	Concrete floor: <b>Compressive strength: ≥ 20 MPa, Tensile strength: ≥ 1.5 Mpa.</b> The floor surface must be flat, steady and dry and clean. The cracks, defects should be completely treated.
<b>Mixing:</b>	Firstly, mixing part A and part B, and continue mixing with part C by an electric mixer or special blender at low speed (300÷400 rpm) about 05 minutes or longer until material is homogeneous. If need to split quantity of material, should stir part A before weight.
<b>Application:</b>	Pour the mixed mixture onto the corresponding surface area to each parallel rows with width 200 ÷ 300 mm, using a jagged scraper to spread out materials according to the thicknes required. Using a notched roller to support the leveling and get rid of air bubbles. <b>Note:</b> While the mixture is not hardening, the application space should be no dust, avoid insects.
<b>Cleaning:</b>	Use dry cloth and BestThinner SC01 to clean equipments immediately after the execution and before the mixture's hardening.
<b>Safety:</b>	BestCoat EP609 is non toxic, non flammable. However, should wear gloves, masks and glasses while handling the product. In case of accidental eye contact, wash with fresh water and seek medical advice immediately.
<b>Disclaimer:</b>	<i>The technical information and application instructions in documents of BESTMIX are based on BESTMIX's current knowledge and practical experience. The information here only describes the general nature of the product, so users should test the product for each purpose. BESTMIX has the right to change the features of our product, user must always refer to the latest technology product.</i>

**PHỤ GIA & HÓA CHẤT XÂY DỰNG BESTMIX® CONSTRUCTION CHEMICALS & ADMIXTURES**  
 PHỤ GIA BÉ TÔNG, XI MÀNG - HÓA CHẤT CHỐNG THẤM - VỮA RỐT RỐT KHÔNG CO NGÓT - KẾT NỐI - TRÁM BÍT - SỬA CHỮA - BẢO VỆ AN THIÊN ★ CEMENT AID - CONCRETE ADMIXTURE - WATERPROOFING - GROUTING - FLOORING - BONDING - SEALING - REPAIRING - PROTECTING - FINISHING

**BESTMIX CORPORATION**

www.bestmix.vn

**HEAD OFFICE:**  
 Lot D1, D1&N3 Rd., Nam Tan Uyen IP,  
 Tan Uyen Town, Binh Duong Province,  
 Tel: (027) 4365 3990 - 4365 3991  
 Email: info@bestmix.com.vn

**HCMC OFFICE 1:**  
 378-384 Cong Hoa Str., Ward 13,  
 Tan Binh Dist., Ho Chi Minh City  
 Tel: (028) 3810 7995 (7996, 7997)  
 Email: bm1@bestmix.com.vn

**HCMC OFFICE 2:**  
 23 Nguyen Huu Canh Str., Ward 22,  
 Binh Thanh Dist., Ho Chi Minh City  
 Tel: (028) 3899 0339 - 3899 0340  
 Email: bm2@bestmix.com.vn

**NHA TRANG OFFICE:**  
 989 Le Hong Phong Street,  
 Phuoc Long Ward, Nha Trang City  
 Tel: 090 545 3579  
 Email: bm3@bestmix.com.vn

**CENTRAL BRANCH:**  
 478B1 Dien Bien Phu Street,  
 Thanh Khe District, Da Nang City  
 Tel: (023) 6371 5299 - 6371 5399  
 Email: bm4@bestmix.com.vn

**NORTHERN BRANCH:**  
 TT6.2 - 65, Dai Kim Urban Area,  
 Hoang Mai District, Ha Noi City  
 Tel: (024) 3200 8234  
 Email: bm5@bestmix.com.vn