

2018 Version

# BestGrout CE800

No shrinkage Grout, Modified Polymer-Cement based.

<b>Description:</b>	BestGrout CE800 is a high compressive strength, non-shrinkage, flowable, cement-based compound, supplied in premixed powder, ready to use. It consists special Portland cement, selected quartz sand and special chemicals.
<b>Uses:</b>	BestGrout CE800 is recommended for use such as: <ul style="list-style-type: none"><li>✓ Anchoring bolts, heavy machinery assembling, pointing.</li><li>✓ Mounting plates of construction posts, and keys of bridges.</li><li>✓ Sealing joints of concrete pipes.</li><li>✓ Filling large slots, big concrete honeycombs...</li><li>✓ Patching eroded concrete...</li><li>✓ Special precast concrete members.</li></ul>
<b>Advantages:</b>	<ul style="list-style-type: none"><li>✓ Very high and consistent mechanical properties.</li><li>✓ Excellent workability, and flow ability.</li><li>✓ Good self-leveling, and compacting characteristics.</li><li>✓ Non-shrinking, expanding mortar.</li><li>✓ Very easy application.</li><li>✓ Non-toxic.</li><li>✓ Chloride-free, non-corrosion to reinforced steel bars.</li></ul>

## SPECIFICATION

<b>Color/Supply form:</b>	Cement grey color/Dry powder.
<b>Package:</b>	25 kg/bag.
<b>Shelf life:</b>	12 months from the produced date in the right storage conditions.
<b>Bulk density:</b>	1.6 kg/liter
<b>Specific density:</b>	Dry powder: 2.85 kg/liter                      grout: 2.20 kg/liter
<b>Consumption:</b>	1.92 kg/liter. Need 77 bags for 1m <sup>3</sup> mortar.
<b>Application temperature:</b>	Minimum ambient temperature to apply: 15°C
<b>Waterproof resistance:</b>	Reinforce the waterproof resistance for structures.
<b>Mechanical strength:</b>	Increase the mechanical impact resistance.
<b>Application time:</b>	Within 15 minutes after mixing.

## BESTMIX CORPORATION

www.bestmix.vn

**HEAD OFFICE:**  
Lot D1, D1&N3 Rd., Nam Tân Uyên IP,  
Tân Uyên Town, Bình Dương Province,  
Tel: (027) 4365 3990 - 4365 3991  
Email: info@bestmix.com.vn

**HCMC OFFICE 1:**  
378-384 Cong Hoa Str., Ward 13,  
Tan Binh Dist., Ho Chi Minh City  
Tel: (028) 3810 7995 (7996, 7997)  
Email: bm1@bestmix.com.vn

**HCMC OFFICE 2:**  
23 Nguyen Huu Canh Str., Ward 22,  
Binh Thanh Dist., Ho Chi Minh City  
Tel: (028) 3899 0339 - 3899 0340  
Email: bm2@bestmix.com.vn

**NHA TRANG OFFICE:**  
989 Le Hong Phong Street,  
Phuoc Long Ward, Nha Trang City  
Tel: 090 545 3579  
Email: bm3@bestmix.com.vn

**CENTRAL BRANCH:**  
478B1 Dien Bien Phu Street,  
Thanh Khe District, Da Nang City  
Tel: (023) 6371 5299 - 6371 5399  
Email: bm4@bestmix.com.vn

**NORTHERN BRANCH:**  
TT6.2 - 65, Dai Kim Urban Area,  
Hoang Mai District, Ha Noi City  
Tel: (024) 3200 8234  
Email: bm5@bestmix.com.vn

