

BestSeal SS50W

Modified Silane water repellents, water dispersing

Description:

- BestSeal SS50W is a highly active modified Silanes-based concentrated waterproofing compound, water-dispersing, fast-acting in alkaline environments such as cement...
- When BestSeal SS50W is mixed with a hydraulic binder such as cement, lime, or gypsum... will form transparent inorganic polymeric membrane Silanes, multi-linking, and longevity.
- BestSeal SS50W has the effect of making the surface of the material very water resistant with the lotus leaf effect, making water molecules impermeable from the outside but still allowing steam to escape from the inside out through pores, capillaries or tiny cracks, so it does not cause blistering or change surface appearance.

Recommended uses:

BestSeal SS50W is used for specialized waterproofing for most alkaline (basic) materials such as:

- Concrete, mortar, oil paste...from cement, lime, gypsum.

Advantage:

- High waterproofing ability.
- Quick reaction, longevity.
- Stable quality, high economic efficiency.
- Weather resistant, does not decompose or age under the effect of UV rays.
- Does not affect the adhesion ability if the material is protected and properly cured.
- Able to steam out so it won't peel, or blister, and minimize the damage, and growth of moss and mold.
- Does not change the color and finished appearance of the surface.
- Widely applicable to many different materials.
- Simple, easy to use, odorless, non-toxic, and environmentally friendly.

PRODUCT INFORMATION:**Suppliers form:** Milky white liquid.**Density:** 0.97 ± 0.02 kg/liter at 25°C**Chemical based:** Modified Silanes**Active content:** ≥ 50 %**Consumption:** 0.05% to 0.10% by weight of dry material. Depending on the material and the level of waterproofing required, this rate of use may vary.**Packaging:** 25 liters/ can; 210 liters/ drum; 1000 liters/ IBC tank or as requested.**Storage condition:** Cool, dry place, avoid sunlight, ambient temperature is 10°C ÷ 30°C**Shelf-life:** At least 6 months from the date of manufacture (in a sealed container, under the above storage condition)**BESTMIX CORPORATION**

www.bestmix.vn

HEAD OFFICE:
Lot D1, D1&N3 Rd., Nam Tan Uyen IP,
Tan Uyen Town, Binh Duong Province.
Tel: (027) 4365 3990 - 4365 3991
Email: info@bestmix.com.vn

HCMC OFFICE 1:
378-384 Cong Hoa Str., Ward 13,
Tan Binh Dist., Ho Chi Minh City
Tel: (028) 3810 7995 (7996, 7997)
Email: bm1@bestmix.com.vn

HCMC OFFICE 2:
23 Nguyen Huu Canh Str., Ward 22,
Binh Thanh Dist., Ho Chi Minh City
Tel: (028) 3899 0339 - 3899 0340
Email: bm2@bestmix.com.vn

NHA TRANG OFFICE:
989 Le Hong Phong Street,
Phuoc Long Ward, Nha Trang City
Tel: 090 545 3579
Email: bm3@bestmix.com.vn

CENTRAL BRANCH:
478B1 Dien Bien Phu Street,
Thanh Khe District, Da Nang City
Tel: (023) 6371 5299 - 6371 5399
Email: bm4@bestmix.com.vn

NORTHERN BRANCH:
TT6.2 - 65, Dai Kim Urban Area,
Hoang Mai District, Ha Noi City
Tel: (024) 3200 8234
Email: bm5@bestmix.com.vn

GUIDE TO APPLICATION:

Mixing:	BestSeal SS50W is pre-quantity and premixed with water.
Caution:	The material must be properly moistened during the curing period. Because when the material is dry, it will completely prevent the penetration of water from the outside, causing a lack of water to maintain the material. Shake (or stir) well before use. Close the lid of the container immediately after use.
Health and safety:	BestSeal SS50W does not cause fire or explosion. BestSeal SS50W may cause allergic reactions to sensitive skin with prolonged exposure. PPES should be worn when working with the product. When it gets into the eyes, nose, or mouth... should immediately wash with clean water many times first when going to the nearest medical facility for timely and proper treatment methods.

Disclaimer:

The technical information and manuals in the BESTMIX documents are based on our knowledge and practical experience. The information contained herein is of a general nature only. Before use, it is necessary to conduct tests to check the suitability of products for each specific requirement and purpose. BESTMIX reserves the right to change the physical parameters of the product without prior notice. The user should always refer to the product's latest technical documentation.

BESTMIX CORPORATION

www.bestmix.vn

HEAD OFFICE:

Lot D1, D1&N3 Rd., Nam Tan Uyen IP,
Tan Uyen Town, Binh Duong Province.
Tel: (027) 4365 3990 - 4365 3991
Email: info@bestmix.com.vn

HCMC OFFICE 1:

378-384 Cong Hoa Str., Ward 13,
Tan Binh Dist., Ho Chi Minh City
Tel: (028) 3810 7995 (7996, 7997)
Email: bm1@bestmix.com.vn

HCMC OFFICE 2:

23 Nguyen Huu Canh Str., Ward 22,
Binh Thanh Dist., Ho Chi Minh City
Tel: (028) 3899 0339 - 3899 0340
Email: bm2@bestmix.com.vn

NHA TRANG OFFICE:

989 Le Hong Phong Street,
Phuoc Long Ward, Nha Trang City
Tel: 090 545 3579
Email: bm3@bestmix.com.vn

CENTRAL BRANCH:

478B1 Dien Bien Phu Street,
Thanh Khe District, Da Nang City
Tel: (023) 6371 5299 - 6371 5399
Email: bm4@bestmix.com.vn

NORTHERN BRANCH:

TT6.2 - 65, Dai Kim Urban Area,
Hoang Mai District, Ha Noi City
Tel: (024) 3200 8234
Email: bm5@bestmix.com.vn