

Jan 2022 Version

BestTile CE075

Tile adhesive, modified the cement-polymer base, One component.

Description: BestTile CE075 is tile adhesive, modified cement-polymer, ready mixed, one component. Mixing with water to use.
BestTile CE075 is made of special cement, selected siliceous aggregate and special additives, polymer modified.

Recommended for:

- Tile, floor, terrace,...
- Tile wall type: vertical wall, tilt wall,...
- Decorative tile, antique brick and concrete,...
- Roofing tile, decorative tile in special cases.
- Mineral fiber plate panels used for sound insulation, heat,...

Advantage:

- High plasticity, high adhesion, application and modification time is long, easy to apply, saving material and labor.
- Higher waterproofing ability than traditional mortar because the component contains special additives.
- Ready mixed, one component, regularly quantitative of components should be easy to use, avoid risks in the process of preparation on site.
- The strength develops fast and highly, put into use early.
- Improve the aesthetic value for the project.
- Non-toxic, can be used for domestic water tanks.
- Does not contain chloride corrosion of reinforcement .
- Suitable climatic conditions.

TECHNICAL DATA:

Existence form:	Dry powder.
Color:	Grey, other colors upon request.
Compressive strength:	≥ 7.5 MPa.
Bonding strength:	~ 1.0 MPa.
Density:	Dry powder: 2.60 ± 0.02 kg/liter. Wet powder: 1.80 ± 0.02 kg/liter .
Water ratio:	20 22 % compared with powder weight.
Consumption:	Average: 1.65 kg dry powder/1m ² /1mm.
Holding conditions:	Unopened bag, moisture resistance, take a dry and cool place.
Shelf life:	At least 12 months from the date of manufacture.
Package:	25 kg/bag.

BESTMIX CORPORATION

www.bestmix.vn

HEAD OFFICE:
Lot D1, D1&N3 Rd., Nam Tan Uyen IP,
Tan Uyen Town, Binh Duong Province.
Tel: (027) 4365 3990 - 4365 3991
Email: info@bestmix.com.vn

HCMC OFFICE 1:
378-384 Cong Hoa Str., Ward 13,
Tan Binh Dist., Ho Chi Minh City
Tel: (028) 3810 7995 (7996, 7997)
Email: bm1@bestmix.com.vn

HCMC OFFICE 2:
23 Nguyen Huu Canh Str., Ward 22,
Binh Thanh Dist., Ho Chi Minh City
Tel: (028) 3899 0339 - 3899 0340
Email: bm2@bestmix.com.vn

NHA TRANG OFFICE:
989 Le Hong Phong Street,
Phuoc Long Ward, Nha Trang City
Tel: 090 545 3579
Email: bm3@bestmix.com.vn

CENTRAL BRANCH:
478B1 Dien Bien Phu Street,
Thanh Khe District, Da Nang City
Tel: (023) 6371 5299 - 6371 5399
Email: bm4@bestmix.com.vn

NORTHERN BRANCH:
TT6.2 - 65, Dai Kim Urban Area,
Hoang Mai District, Ha Noi City
Tel: (024) 3200 8234
Email: bm5@bestmix.com.vn

GUIDE TO APPLICATION:

PHỤ GIA & HÓA CHẤT XÂY DỰNG BESTMIX® CONSTRUCTION CHEMICALS & ADMIXTURES
 PHỤ GIA BÉ TÔNG, XI MÀNG - HÓA CHẤT CHỐNG THẤM · VỮA RỐT RỐT KHÔNG CO NGÓT · NỀN SÀN · KẾT NỐI · TRÁM BÍT · SỬA CHỮA · BẢO VỆ AN TIỀN · CEMENT AID · CONCRETE ADMIXTURE · WATERPROOFING · GROUTING · FLOORING · BONDING · SEALING · REPAIRING · PROTECTING · FINISHING

Substrate preparation:	The surface should be cleaned as required, dirt, moss, and mold,...to be completely removed by appropriate means. In particular, if the surface is contaminated with oil, or grease,... be thoroughly treated before applying BestTile CE075. Should wet the surface before applying for at least 05 minutes.
Mixing:	Use a clean basket with appropriate capacity, pour the mixing water before, set stirring speed to 300 ÷ 400 circles/mins, run and continue to pour slowly BestTile CE075 while mixing until homogeneous. Mixing time is around 05 minutes. However, depending on the specific conditions to determine the appropriate mixing time to ensure homogenous mixtures, without lumps.
Application:	Use an iron brush or plastic with an appropriate sawtooth to apply compound BestTile CE075 on the surface. The tile work is carried bottom-up and horizontal application. Use a rubber hammer and other tools to edit the appropriate location of bricks as desired. The time allowed for application and editing can be extended to 30 minutes from mixing BestTile CE075 with water. However, this depends on the environmental condition of temperature, wet surface condition,... Note: The application time and editing are not over 60 minutes from mixing. Do not add any other materials into BestTile CE075 when using(except mixing water). Do not apply product after expired application time.
Curing:	Curing regular requirements as other cement base products. Avoid construction surfaces being lost water rapidly by direct contact with sunlight or wind.. Moisten the surface frequently within 07 days.
Cleaning:	Clean tools and equipment after application and before material sets.
Safety:	BestTile CE075 is non-toxic. However, it could make an allergy to sensitive skin. Do not contact it for a long time. Should wear labor protection when applicable. Avoid contacting directly food, instruments of live activity, and keep out of the reach of children. In case of accidental eye contact, wash with fresh water and seek medical advice immediately.
Disclaimer:	<i>The technical information and application instruction in documents of BESTMIX based on BESTMIX's current knowledge and practical experience. The information here only describes the general nature of product, so users should test the product for each purpose. BESTMIX has the right to change features of our product, user must always refer the latest technology product.</i>